



# Chilli Control Panels

## Installation Dimming Range

### Key Features

- Slimline design
- Illuminated buttons
- Up to 4 panels per dimmer
- Controls multiple dimmers simultaneously
- Brushed stainless steel and polished brass finishes
- Simple connections
- Uses standard CAT5 cable

### Ordering Information

10, 5 & 2 button - in Stainless Steel or brass  
Last Man Out with Keyswitch - Stainless Steel or brass available

(Contact Zero 88 for further details and order codes)

### Dimensions

#### Single Gang Control Panels

86 (H) x 86 (W) x 27.5mm (D)  
Weight: 0.12Kg

#### Last Man Out Panel

86 (H) x 146 (W) x 27.5mm (D)  
Weight: 0.25Kg



### Overview

The Chilli Control Panels can be employed where simple scene setting is required. Available in a variety of configurations, the control panels provide direct access to the internal memories and sequences of the dimmer. Panels can be assigned to any one of the 10 areas.

Available in 2, 5 and 10 button configurations, the panels have been designed to fit any standard UK single gang back box allowing simple installation and are available in brushed stainless steel or brushed brass with illuminated buttons. Up to 50 Chilli Control Panels can be used on a single network, providing multi-point control with modern aesthetics.

A Last Man Out panel is also available. This panel features a 5 button control panel and a keyswitch, allowing for a supervisor to turn the network on or off from a single location. When the keyswitch is turned, after a 30 second delay, the panel sends an All Off command to the ChilliNet dimmers. The Last Man Out panel fits a standard UK double gang back box.

### Contact your local Eaton office

Usk House, Lakeside, Llantarnam Park,  
Cwmbran, Torfaen, NP44 3HD. UK  
T: +44 (0)1633 838088 F: +44 (0)1633 867880  
E: enquiries@zero88.com www.zero88.com



**Eaton Industries Manufacturing GmbH**  
Electrical Sector EMEA  
Route de la Longeraie  
71110 Morges, Switzerland  
Eaton.eu

© 2015 Eaton  
All Rights Reserved

Chilli\_Control\_Panels\_Datasheet\_UK\_Rev3\_0615

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

