

- [Electrical](#)
- [DMX](#)
- [Mechanical](#)
- [Environmental](#)
- [EMC](#)

Electrical

Supply Voltage:

- 190V - 255V

Supply Frequency:

- 40 to 70 Hz auto-sensing and auto-tracking

Total Dimmer Capacity:

- 120 A (40A per phase, limited to 32A per phase by mains connector)

Channel Capacity

- Minimum: 0.1A
- Maximum: 10A

Rise Time

- 80uS


Channel Protection

10A neutral disconnect thermal magnetic circuit breaker per channel, breaking capacity 6000A.

DMX

- USITT DMX512/1990
- External switchable termination

Mechanical



- Height: 132mm - 3 Rack Units
- Width: 483mm - 19" Rack Mount
- Depth: 420mm
- Weight: 14.5kg
- IP Rating: IP2X (indoor use only)

Environmental

- Operating Temperature Range: +2°C to +40°C
- Operating Relative Humidity: 5% to 95% Non-condensing

Always observe the operating environment information. If this environment is exceeded, it is likely that damage will occur to Spice.

EMC

Low Voltage:

- EN60439-1 1994
- EN60950

Emissions:

- EN55022
- EN55015:2000
- EN61000-3-2

Immunity:

- EN61000-4-3
- EN61000-4-4
- EN61000-4-5
- EN61000-4-6
- EN61000-4-11AC