



Splitter 8

Flexible DMX / RDM splitter & data fix.

Key Features

- 1 input, 8 output DMX / RDM splitting
- Fully RDM compatible
- "Fix Switch" for data-fixing
- Opto Isolated Input
- Electrically (transient) protected outputs
- Desk Mount or 1RU 19" Form Factor
- Neutrik 5pin XLR connectors
- IEC power connector
- 3 year warranty
- CE compliant to all relevant standards



Overview

Splitter 8 provides flexible DMX / RDM data distribution in a slim (1RU) 19" format, offering both splitter and "data fix" functionality in a single device.

Splitter 8 is fully compatible with the latest RDM protocol, ensuring your DMX distribution network is ready to meet your future demands. Splitter 8 is appropriate for permanent installations or as a flexible, adaptable rental & touring tool (due to the narrow depth, two units will fit into a single 1RU slot of a doubled-sided rack).

"Fix Switch" is designed for systems where compatibility issues (or poorly designed fixtures) are causing flickering. When enabled, "Fix Switch" discards non-DMX data (including RDM) and adjusts the DMX timing to values more likely to work with fixtures that do not fully comply with the DMX standard.

The input is optically isolated, with a "Thru" connection for further expansion. The eight buffered outputs are protected against electrical faults. All connectors are Neutrik parts.

Splitter 8 is ideal for use alongside Gateway 4 and Gateway 8 to build a larger data distribution system.

Ordering Information

0050-000074-00	Splitter 8 UK
0050-000075-00	Splitter 8 Schuko/French
0050-000076-00	Splitter 8 US




Supplied Accessories

IEC Mains Lead

Specifications

- 19" 1U Rack metal Enclosure
- Desktop or 19" Rack Mounting
- Made in the United Kingdom
- Supply Voltage: 100 - 230 VAC
- Input power (max): 250 W
- Duty cycle: 100% @ 25°C
- Internal fuse: T1A slow blow
- Operating Temperature: 0°C to 40°C
- Storage Temperature: -10°C to +50°C
- Operating Relative Humidity (max): 80% Non Condensing
- IP Rating: IP20 Indoor Use Only
- Certification: CE, WEEE, RoHS
- 3 year warranty
- Optically isolated input
- Split/Fix selector
- LEDs for Power & Data
- Input/Output protocols:
 - DMX512
 - DMX512 (1990)
 - DMX512-A
 - RDM V1.0 (E1.20 - 2010 ESTA Standard)

Dimensions



Weight: 1.8Kg

Contact your local Eaton office

T: +44 (0)1923 495495 F: +44 (0)1633 867880
E: enquiries@zero88.com www.zero88.com

Eaton Lighting Systems
Usk House, Lakeside,
Llantarnam Park,
Cwmbran, Torfaen, NP44 3HD. UK
eatonlightingsystems.com

© 2019 Eaton
All Rights Reserved

Splitter_8_UK_Rev1_1119

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.